

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously Presented) An apparatus for producing alcohol from cereal raw materials, comprising
 - a grinding station (1) which grinds to flour at least the grain comprising a starch and/or sugar of the cereal raw materials,
 - a liquefaction station (9) which digests flour to a liquefied raw material,
 - a fermentation station (13) which ferments said liquefied raw material to mash,
 - a distillation station (15) separating off alcohol from the mash, and
 - a drying station (21, 31) for drying vinasse arising in the distillation station (15),wherein the grinding station (1) separates at least a part of the seed coat portions enclosing the grain, and the separated seed coat portions are fed to the drying station (21, 31) as carrier medium for the vinasse drying, and wherein said drying station (21, 31) comprises a drier (21) which carries out the final drying of the vinasse produced as a residue in said distillation station (15) at a dew point temperature of above 95°C, and wherein the distillation station (15) comprises a distillation column (91) heated by the vapor of the drier (21).
2. (Original) The apparatus as claimed in claim 1, characterized in that the grinding

station (1) separates off the seed coat portions in a weight ratio of seed coat portions to flour of 1 to 9 to 2 to 8.

3. (Previously Presented) The apparatus as claimed in claim 1, characterized in that the grinding station (1) grinds the cereals to flour with a mean particle size between 0.5 and 1 mm.
4. (Previously Presented) The apparatus as claimed in claim 1, characterized in that the grinding station (1) has a roller mill or an impact jet mill.
5. (Previously Presented) The apparatus as claimed in claim 1, wherein said liquefaction station (9) comprises at least one mixing stage comprising a mixing condenser (53) for admixing steam to a product stream of the ground cereal raw material or a suspension thereof, a steam-jet injector (57) downstream of the mixing condenser (9) for admixing superheated steam to the product stream, and an expansion cooler (63) for the product stream connected downstream of the steam-jet injector (57) and comprises at least one expansion stage (67, 73), said mixing condenser (53) admixing expansion vapor of said expansion cooler (63) to said product stream.
6. (Previously Presented) The apparatus as claimed in claim 5, wherein said expansion cooler (63) is of multistage construction.

7. (Original) The apparatus as claimed in claim 6, characterized in that the mixing condenser (53) is of single-stage construction, and the expansion cooler (63) is of two-stage construction.
8. (Previously Presented) The apparatus as claimed in claim 5, characterized in that the mixing condenser (53) heats the product stream to a temperature below the gelatinization temperature of the raw material, and the steam-jet injector (57) heats the product stream to a temperature above the gelatinization temperature of the raw material.
9. (Previously Presented) The apparatus as claimed in claim 1, characterized in that, between the fermentation station (13) and the distillation station (15), there is disposed a degassing station (17) in which the mash product stream passes through from top to bottom a vertically standing tube bundle (81) which is evacuated at its bottom end, and the mash product stream expands in the tube bundle (81).
10. (Original) The apparatus as claimed in claim 9, characterized in that the mash product stream, before entry into the tube bundle (81), passes through a heat exchanger (79) preheating the mash.
11. (Canceled).

12. (Previously Presented) The apparatus as claimed in claim 1, wherein said drier (21) produces essentially air-free exhaust vapor.
13. (Previously Presented) The apparatus as claimed in claim 1, wherein said drier (21) is constructed as a superheated steam drier.
14. (Previously Presented) The apparatus as claimed in claim 1, characterized in that the distillation station (15) has a first distillation column (91) which is heated, in particular, by exhaust vapor of the drying station (21, 31), to which is connected a dehydration station (45) which dehydrates its crude alcohol product stream
and in that a second distillation column (117) is connected at an intermediate level of the first distillation column (91) above its mash feed level (93), which second distillation column is heated via a heat exchanger (127) by heat of the dehydrated alcohol vapor of the dehydration station (45).
15. (Original) The apparatus as claimed in claim 14, characterized in that the heat exchanger is constructed as a falling-film evaporator (127) heated by dehydrated alcohol vapor of the dehydration station (45).
16. (Previously Presented) The apparatus as claimed in claim 14, characterized in that the dehydration station (45) comprises a molecular sieve (117).

17. (Original) The apparatus as claimed in claim 16, characterized in that the molecular sieve (117) is operated at a pressure of 1.7 bar absolute or more.
18. (Previously Presented) The apparatus as claimed in claim 1, characterized in that the drying station (21, 31) comprises a separator (25) which separates the vinasse into a vinasse-thin juice product stream and a vinasse-solids product stream, an evaporator (31) which evaporates the vinasse-thin juice product stream to form vinasse-thick juice, and also a drier (21) which dries the vinasse-thick juice together with the vinasse-solids to give dry vinasse, in that the distillation station (15) is connected downstream of the dehydration station (45) which dehydrates the crude alcohol product stream and in that the evaporator (31) has at least one evaporator stage (51) heated by heat of the dehydrated alcohol vapor of the dehydration station.
19. (Original) The apparatus as claimed in claim 18, characterized in that the evaporator (31) comprises a pre-evaporator (49) and a final evaporator (51) and in that the final evaporator (51) is heated by dehydrated alcohol vapor from the dehydration station (45).
20. (Previously Presented) The apparatus as claimed in claim 18, characterized in that the dehydration station (45) comprises a molecular sieve (117).

21. (Original) The apparatus as claimed in claim 20, characterized in that the molecular sieve (117) is operated at a pressure of 1.7 bar absolute or more.
22. (Previously Presented) An apparatus for producing alcohol from a cereal grain raw material, comprising
- grinding means for grinding said cereal grain raw material into a flour and separating at least a part of a seed coat portion enclosing said cereal grain raw material,
 - liquefying means for digesting said flour into a liquefied raw material,
 - fermenting means for fermenting said liquefied raw material to form a mash,
 - distillation means comprising a distillation column for separating alcohol from said mash at a dew point temperature of above 95°C,
 - drying means comprising a drier for drying a vinasse formed as a residue in said distillation means and for producing an exhaust vapor for heating said distillation column, and
 - feeding means for feeding dry seed coat portions to said drying means as a carrier medium for said vinasse.
23. (New) The apparatus of claim 1, wherein said final drying of the vinasse is carried out at a dew point temperature of from 100°C to 105°C.